

IFS-402CGS-4PH

4x FE RJ45 + 2x 100/1000 SFP with 4x PoE 120W, Compact size

- ▲ 4KV surge protection for PoE, UTP and SFP ports
- ▲ Wide operating temperature -40 ~ 75° C
- ▲ IP30 rugged metal housing and fanless
- ▲ EN62368-1, EN50121-4, EN61000-6-2, EN61000-6-4, CE and FCC certified



The industrial compact size PoE Ethernet switch, unmanaged plug-and-play easy for use, has 4 10/100 UTP ports and each port supports 30W PoE+. Equipped with two 100/1000 SFP slots for fiber optic connections to meet the requirements for extended transmission distance, fanless design, high MTBF, supports wide operating temperature, redundant 48VDC power input, suitable for heavy-duty applications in harsh environments, such as industrial factory automations, data centers, intelligent transportation systems, military and utility market applications where environmental conditions exceed commercial product specifications.

Features

- Provides 4-port IEEE 802.3at/af PoE output (30W/Per Port)
- Maximum PoE output power budget 120W
- 48VDC (44~57VDC) redundant dual input power
- Supports DIP switch to set broadcast storm protection, SFP Auto/Force Mode, SFP 100M/1000M ; RJ45 Auto/force mode, 10M/100M, Full/half.
- Supports flow control
- Provides broadcast storm protection
- DIN Rail mounting or wall mounting

Specifications

Standard	IEEE 802.3	10Base-T Ethernet
	IEEE 802.3u	100Base-TX and 100Base-FX Fast Ethernet
	IEEE 802.3z	1000Base-X Gigabit Ethernet over fiber-optic
	IEEE 802.3x	Flow Control and Back Pressure
	IEEE 802.3at	PoE+ (Power over Ethernet enhancements)
	IEEE 802.3af	PoE (Power over Ethernet)
	IEEE 802.3af	PoE (Power over Ethernet)
	Switch Architecture	Back-Plane (Switching Fabric): 4.8Gbps (Full Wire-Speed)
Data Processing	Store and Forward	
Flow Control	IEEE 802.3x flow control, back pressure flow control	
MAC Address Table	4K	
Packet Buffer Size	1.75Mbit	
Max Frame Size	1522Bytes	
Jumbo Frame	10K Byte	
PoE standard	IEEE 802.3at/af	


PoE RJ-45 pin Assignment	RJ-45 port #1~#4 support IEEE 802.3at/af End-Span, Alternative A mode		
	Positive (V+): RJ-45 pin 1, 2.		
	Negative (V-): RJ-45 pin 3, 6.		
	Data (1, 2, 3, 6)		
Network Connector	4x RJ-45 for 10/100Base-TX, Auto negotiation Speed or Force Mode, Auto MDI/MDI-X function, Full/Half duplex		
	2x 100/1000Base-X SFP, Auto or Force Mode		
Network Cable	UTP/STP Cat. 5e cable or above		
	EIA/TIA-568 100-ohm (100meter)		
	Fiber Cable (Multi-mode): 50/125um, 62.5/125um / Fiber Cable (Single-mode): 9/125um		
Protocols	CSMA/CD		
LED	System: Power 1 (Green), Power 2 (Green)		
	UTP: 100 Link/Act (Green), 10 Link/Act (Amber)		
	SFP Slot: 100 Link/Active (Green), 1000 Link/Active (Amber)		
	PoE: ON (Green)		
DIP SW	DIP 1	Broadcast Protection OFF : Enable ON : Disable	
	DIP 2	Off: Fiber Auto On: Fiber Force Mode	
	DIP 3	SFP Fiber Speed OFF: Giga ON: 100M	
	DIP 4	RJ45 Mode OFF: Auto ON: Force	
	DIP 5	RJ45 Speed OFF: 100M ON: 10M	
	DIP 6	RJ45 Duplex OFF: Full ON: Half	
Reverse Polarity Protection	Supported for Power Input		
Overload Current Protection	Supported		
Power Supply	Redundant dual 48VDC (44~57VDC) input power (Removable terminal block) (50~57V input is recommended for IEEE802.3at in 30W applications)		
Power Consumption	Input Voltage	Total Power Consumption	Device Power Consumption
	50 VDC	127.5W	5.3W
PoE Power Budget	Maximum PoE Output power budget 120W (30W/Per Port)		
Removable Terminal Block	Provides 2 Redundant power, 4 Pin		
Operating Temperature	-10 ~ 60°C (IFS-402CGS-4PH) -40 ~ 75°C (IFS-402CGS-4PHE)		
Operating Humidity	5% to 95% (Non-condensing)		
Storage Temperature	-40 ~ 85°C		
Housing	Rugged metal, IP30 Protection and fanless		
Dimensions	106x 38.6x 142mm (D X W X H)		
Weight	705g		
Installation Mounting	DIN Rail mounting, or wall mounting (Optional)		
MTBF	823,732Hours (MIL-HDBK-217)		
Warranty	5 years		

Certification

EMC	CE (EN55032, EN55035)
EMI (Electromagnetic Interference)	FCC Part 15 Subpart B Class A, CE
Railway Traffic	EN50121-4
Immunity for Heavy Industrial Environment	EN61000-6-2

Emission for Heavy Industrial Environment	EN61000-6-4
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B
	EN61000-4-3 (RS) Level 3, Criteria A
	EN61000-4-4 (Burst) Level 3, Criteria A
	EN61000-4-5 (Surge) Level 3, Criteria B
	EN61000-4-6 (CS) Level 3, Criteria A
	EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A
Safety	EN62368-1
4KV Surge Protection	Supported for PoE, UTP and SFP port
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-31
Vibration	IEC 60068-2-6

Dimensions



Ordering Information

Model Name	Total Port	RJ45 UTP Port	Fiber Port	PoE Port		Input Power	Certification			Operating Temperature
		10/100 Base-T(X)	100/1000Base-X	IEEE802.3 at/af	Power Budget	Redundant	EN62368-1	EN50121-4	CE, FCC EN61000-6-2 EN61000-6-4	
IFS-402CGS-4PH	6	4	2 SFP	4	120W	48VDC	V	V	V	-10~60°C
IFS-402CGS-4PHE	6	4	2 SFP	4	120W	48VDC	V	V	V	-40~75°C

Optional Accessories

Wall Mount Kit

IND-WMK01 Wall Mount kit for Industrial product (184x30mm) (Narrow)

Industrial SFP Transceiver

The ISFP series of industrial grade SFP modules have been fully tested with all CTC Union industrial grade Ethernet switches for guaranteed compatibility and performance. Best performance can be guaranteed, even in mission-critical applications. (Please see CTC Union's Industrial SFP datasheets for more items and detailed information.)

ISFP-M7000-85-D(E)	Industrial SFP GbE 1000Base-SX, M/M, 500 meter, wave length 850nm, 7.5dB, LC, DDMI, -10~70°C (-40~85°C)
ISFP-S7020-31-D(E)	Industrial SFP 1000Base-LX, S/M, 20km, wave length 1310nm, 15dB, LC, DDMI, -10~70°C (-40~85°C)
ISFP-T7T00-00-(E)	Industrial SFP 10/100/1000Base-T UTP 100meter, -10~70°C (-40~85°C)
ISFP-M5002-31-D(E)	Industrial SFP 155M 100Base-FX, MM, 2km, wave length 1310nm, 12dB, LC, DDMI, -10~70°C (-40~85°C)
ISFP-S5030-31-D(E)	Industrial SFP 155M 100Base-FX, SM, 30km, 1310nm, 19dB, LC, DDMI, -10~70°C (-40~85°C)

Industrial Power Supply

NDR-120-48	Industrial Power, Input 90 ~ 264VAC/127 ~ 370VDC, Output 48VDC, 120W, -20 ~ +70°C (For IFS-402CGS-4PH)
NDR-240-48	Industrial Power, Input 90 ~ 264VAC/127 ~ 370VDC, Output 48VDC, 240W, -20 ~ +70°C (For more ref.)