

# IGS-2408SM-24PH-AA

24x GbE RJ45 + 8x 100/1000 SFP with 24x PoE 150W, 110/220VAC

- ▲ Supports IEEE 1588 PTP V2
- ▲ Supports u-Ring, ERPS, EPS, MSTP, RSTP, STP for redundant cabling
- ▲ EN62368-1, EN50121-4, EN61000-6-2/4, CE and FCC certified
- ▲ 4KV surge protection for PoE, RJ45 and SFP ports



The hardened Layer 2 managed PoE switch IGS-2408SM-24PH-AA up to 24 PoE+/PSE ports to meet the stringent requirements of centralized and mission-critical applications, features 8 100/1000 SFP slots and 24 Gigabit UTP ports, supports IEEE 802.3af/IEEE 802.3at standards, each port provides up to 30 watt power output for connecting heavy industrial PoE equipment, fanless design and isolated redundancy AC power supplies are ideal solutions for smart city, surveillance, intelligent traffic control systems and production automation applications.

## Features

- Maximum up to 24x IEEE 802.3af / 802.3at PoE+ output, 30W per port, 150W PoE power budget in total
- Redundant dual input power 110/240VAC
- STP, RSTP, MSTP, ITU-T G.8032 Ethernet Ring Protection Switching (ERPS) for network redundancy
- Provides 5 instances each can support  $\mu$ -Ring,  $\mu$ -Chain or Sub-Ring for flexible networking applications
- $\mu$ -Ring redundancy, recovery time <20ms in 250 devices
- Supports IEEE 1588 PTP V2 for precise time synchronization to operate in Ordinary-Boundary, Peer to Peer Transparent Clock, End to End Transparent Clock, Master, Slave mode by each port
- Supports EMS Management

## Specifications

Standard	IEEE 802.3	10Base-T 10Mbit/s Ethernet
	IEEE 802.3u	100Base-TX, 100Base-FX, Fast Ethernet
	IEEE 802.3ab	1000Base-T Gbit/s Ethernet over twisted pair
	IEEE 802.3z	1000Base-X Gbit/s Ethernet over Fiber-Optic
	IEEE 802.1d	STP (Spanning Tree Protocol)
	IEEE 802.1w	RSTP (Rapid Spanning Tree Protocol)
	IEEE 802.1s	MSTP (Multiple Spanning Tree Protocol)
	ITU-T G.8032 / Y.1344	ERPS (Ethernet Ring Protection Switching)
	ITU-T G.8031 / Y.1342	EPS (Ethernet Protection Switching)
	IEEE 802.1Q	Virtual LANs (VLAN)
	IEEE 802.1X	Port based and MAC based Network Access Control, Authentication
	IEEE 802.3ac	Max frame size extended to 1522Bytes
	IEEE 802.3ad	Link aggregation for parallel links with LACP(Link Aggregation Control Protocol)
	IEEE 802.3af	PoE (Power over Ethernet)
	IEEE 802.3at	PoE+ (Power over Ethernet enhancement)
	IEEE 802.3X	Flow control for full duplex
	IEEE 802.1ad	Stacked VLANs, Q-in-Q
	IEEE 802.1p	LAN Layer 2 QoS/CoS Protocol for Traffic Prioritization
	IEEE 802.1ab	Link Layer Discovery Protocol (LLDP)
	IEEE 802.3az	EEE (Energy Efficient Ethernet)

# Industrial GbE PoE Switch

VLAN ID	4094 IEEE802.1Q VLAN VID
Switch Architecture	Back-plane (Switching Fabric): 64Gbps (Full wire-speed)
Data Processing	Store and Forward
Network Connector	<b>SFP:</b> 8x 100/1000Base-X SFP socket, Support DDMI <b>RJ45:</b> 24x 10/100/1000Base-T RJ-45 Support Auto negotiation speed, Auto MDI/MDI-X function <b>PoE:</b> 24x IEEE 802.3af /IEEE 802.3at PoE+, End-Span, Alternative A mode. Maximum 30W per port, 150W PoE power budget in total <b>RJ45 Pin Assignment:</b> PoE Positive (V+) : RJ-45 pin 1, 2. PoE Negative (V-) : RJ-45 pin 3, 6. Data (1, 2, 3, 6, 4, 5, 7, 8)
Console	RS-232 (RJ-45)
Network Cable	UTP/STP Cat.5e cable or above EIA/TIA-568 100-ohm (100meter)
Protocols	CSMA/CD
Reverse Polarity Protection	For input power
Overload Current Protection	Supported
Power Supply	Redundant dual input power 110/240VAC (Built in 2x 450W AC to DC power supply inside)
Power Consumption	< 33W without PoE load < 206W with 150W PoE load
PoE Power Budget	150W
LED	System: Power 1 (Green), Power 2 (Green), Act /Alarm (Green/Amber), Ring Master (Green) <b>P1~P24</b> UTP: 10/100 Link/Active (Green), 1000 Link/Active (Amber) <b>P25~P32</b> SFP Slot: Link/Active (Amber) PoE (P1~P24): PoE ON (Green)
Jumbo Frame	10K Byte
MAC Address Table	32K
Memory Buffer	4M Bytes for packet buffer
Device Memory	16M Bytes Flash ROM, 1G Bytes RAM
Warning Message	System Syslog, SMTP/ e-mail event message, alarm relay
Alarm Relay Contact	Relay outputs with current carrying capacity of 1A @24VDC, 2-Pin removable terminal block
Operating Temperature	-40 ~ 60°C
Operating Humidity	5% to 95% (Non-condensing)
Storage Temperature	-40 ~ 85°C
Housing	Rugged Metal, IP30 Protection, Fanless
Dimensions	330 x 440 x 44mm (D x W x H)
Weight	5.2kg
Installation Mounting	19" rack mount
MTBF	43,259 Hours (MIL-HDBK-217)
Warranty	5 years

## Certification

EMC	CE (EN55032, EN55035)
EMI (Electromagnetic Interference)	FCC Part 15 Subpart B Class A, CE
Railway Traffic	EN50121-4
Immunity for Heavy Industrial Environment	EN61000-6-2
Emission for Heavy Industrial Environment	EN61000-6-4

EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B
	EN61000-4-3 (RS) Level 3, Criteria A
	EN61000-4-4 (Burst) Level 3, Criteria A
	EN61000-4-5 (Surge) Level 3, Criteria B
	EN61000-4-6 (CS) Level 3, Criteria A
	EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A
Safety	EN62368-1
Surge Protection	4KV for PoE, RJ45 and SFP ports
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6

## Software Specifications

### Topology

VLAN	IEEE 802.1q VLAN, up to 4094 802.1Q VLAN VID
	IEEE 802.1q VLAN, up to 4094 Groups
	IEEE 802.1ad Q-in-Q
	MAC-based VLAN, up to 256 entries
	IP Subnet-based VLAN, up to 128 entries
	Protocol-based VLAN(Ethernet, SNAP, LLC), up to 128 entries
	VLAN Translation, up to 256 entries
	Private VLAN for port isolation
	GVRP (GARP VLAN Registration Protocol)
	MVR (Multicast VLAN Registration)
Link Aggregation (Port Trunk)	Voice VLAN
	Static (Hash with SA, DA, IP, TCP/UDP port), up to 16 trunk group
	Dynamic (IEEE 802.3ad LACP), up to 16 trunk group
Spanning Tree	Per group up-to 8 port
	IEEE 802.1d STP, IEEE 802.1w RSTP, IEEE 802.1s MSTP
Multiple $\mu$ -Ring	Up to 5 instances each support $\mu$ -Ring, $\mu$ -Chain or Sub-Ring for flexible networking applications
	Recovery time <20ms
	The maximum number of device is allowed 250 in a Ring.
Loop Protection	Supported
ITU-T G.8032 / Y.1344 ERPS (Ethernet Ring Protection)	Recovery time <50ms
	Single Ring, Sub-Ring, Multiple ring topology
ITU-T G.8031 / Y.1342 EPS (Ethernet Protection Switching)	Supported

### QoS Features

Class of Service	IEEE 802.1p 8 active priorities queues per port
Traffic Classification QoS	IEEE 802.1p based CoS
	IP Precedence based CoS
	IP DSCP based CoS
	QCL(QoS Control List): Frame Type, Source/Destination MAC, VLAN ID, PCP, DEI Protocol, Source IP, IP Fragment, DSCP, TCP/UDP port number
Bandwidth Control for Ingress	Per port based
Bandwidth Control for Egress	Per port based
	Per queue / Per port shaper
DiffServ (RF 2474) Remarking	
Storm Control	for Unicast, Broadcast, Multicast

## IP Multicasting Features

IGMP / MLD Snooping	IGMP Snooping v1, v2, v3 / MLD Snooping v1, v2
	Port Filtering Profile
	Throttling, Fast Leave
	Maximum Multicast Group : up to 1022 entries
	Query / Static Router Port

## Security Features

IEEE 802.1X	Port-Based MAC-Based
ACL	Number of rules : up to 256 entries for L2 / L3 / L4 L2 : Mac address SA/DA/VLAN L3 : IP address SA/DA, Subnet L4 : TCP/UDP
RADIUS	Authentication & Accounting
TACACS+	Authentication, Authorization, Accounting
HTTPS, HTTP	Supported
SSL / SSH v2	Supported
User Name Password Authentication	Local Authentication Remote Authentication (via RADIUS / TACACS+)
Management Interface Access Filtering	Web, Telnet / SSH , CLI RS-232 console

## Management Features

CLI	Cisco® like CLI
Web UI	Supported
Telnet	Server
SNMP	V1, V2c, V3
sFlow	Supported
Modbus/TCP	Support management and monitoring
SW & Configuration Upgrade	TFTP, HTTP Redundant firmware in case of upgrade failure
RMON	RMON I (1, 2, 3, 9 group), RMON II
MIB	RFC1213 MIB II, Private MIB
UPnP	Supported
DHCP	Server, Client, Relay, Relay option 82, Snooping
IP Source Guard	Supported
Mirroring	Local and Remote
Event Syslog	Syslog server (RFC3164)
Warning Message	System syslog, e-mail, alarm relay
DNS	Client, Proxy
IEEE1588 PTP V2	Supports 5 operating mode in each port : Ordinary-Boundary, Peer to Peer Transparent Clock, End to End Transparent Clock, Master and Slave
NTP V4.0, SNTP	Client
LLDP (IEEE 802.1ab)	Link Layer Discovery Protocol LLDP-MED


## IPv6 Features

IPv6 Management	Telnet Server/ICMP v6
SNMP over IPv6	Supported
HTTP over IPv6	Supported
SSH over IPv6	Supported
IPv6 Telnet	Supported
IPv6 NTP, SNTP	Client

# Industrial GbE PoE Switch

IPv6 QoS	Supported
IPv6 ACL	Number of rules: up to 256 entries for L2 / L3 / L4 L2 : Mac address SA/DA/VLAN L3 : IP address SIP, Subnet (32bit) L4 : TCP/UDP
Advanced PoE Management	PoE PD failure auto checking, and auto reset when PD fail PoE port on/off weekly scheduling PoE Configuration PoE Enable/Disable Power limit by classification Power limit by management Total PoE Power budge limitation maximum 150W Power feeding priority
Other Features	<b>Green Ethernet</b> Supports IEEE 802.3az EEE (Energy Efficient Ethernet) Management to optimize the power consumption Determine the cable length and lowering the power for ports with short cables Lower the power for a port when there is no link LED Power Management : Adjustment LEDs intensity <b>Cable Diagnostic</b> Measuring UTP cable normal or broken point distance

## Dimensions



## Ordering Information

Model Name	Managed	Total Port	RJ45		SFP		PoE		Input Power	Certification				Operating Temperature
			10/100/1000 Base-T(X)	100/1000 Base-X	IEEE802.3 af/at	Power Budget	110/220VAC	Safety EN62368-1		EN50121-4	EN61000-6-2	EN61000-6-4	CE, FCC	
IGS-2408SM-24PH-AA	V	32	24	8	24	150W	2	V	V	V	V	V	-40~60°C	

## Optional Accessories

### Industrial SFP Transceiver

The ISFP series of industrial grade SFP modules have been fully tested with all CTC Union industrial grade Ethernet switches for guaranteed compatibility and performance. Best performance can be guaranteed, even in mission-critical applications. (Please see CTC Union's Industrial SFP datasheets for more items and detailed information.)

ISFP-M7000-85-D(E)	Industrial SFP GbE 1000Base-SX, M/M, 500 meter, wave length 850nm, 7.5dB, LC, DDMI, -10~70°C (-40~85°C)
ISFP-S7020-31-D(E)	Industrial SFP 1000Base-LX, S/M, 20km, wave length 1310nm, 15dB, LC, DDMI, -10~70°C (-40~85°C)
ISFP-T7T00-00-(E)	Industrial SFP 10/100/1000Base-T UTP 100meter, -10~70°C (-40~85°C)
ISFP-M5002-31-D(E)	Industrial SFP 155M 100Base-FX, MM, 2km, wave length 1310nm, 12dB, LC, DDMI, -10~70°C (-40~85°C)
ISFP-S5030-31-D(E)	Industrial SFP 155M 100Base-FX, SM, 30km, 1310nm, 19dB, LC, DDMI, -10~70°C (-40~85°C)